



The Drive to Win



IDM_{SA}

Single-Axis DS402

EtherCAT[®]-based Drive Node

Product Highlights

- > Advanced Servo Control Algorithms for Maximum Motion Performance
 - Non-Linear Control
 - Cascaded Dual Loop Control
 - Customized Algorithms (contact ACS)
- > Universal Motor and Encoder Support for Maximum Flexibility
- > Max Drive Current: 10/20A at 150VDC, 15/30A at 100VDC
- > Drive Supply Input: 12-150Vdc
- > Analog I/O: 1/1
- > Feedback Channels: 2 (AqB, SinCos, or Absolute)
- > SPI Interface for Integrating Sensor Data into Custom Servo Algorithms
- > Digital I/O: 4/3
 - Any can be used for general purpose
 - 1 High-Speed Position Capture (MARK) Input
 - 1 High-Speed Position Event Generation (PEG) Output
 - 2 Limit Sensor Inputs
 - 1 Brake Output
 - 1 General Purpose Output
 - 1 General Purpose Input
- > Functional Safety: STO, SS1

The **IDM_{SA}** is a member of the Intelligent Drive Module (IDM) series of EtherCAT[®] DS402 drives designed to meet the needs of OEMs employing EtherCAT-based control systems with high-precision motion stages. Controllable by any EtherCAT master, its unique multi-processor architecture leverages powerful control algorithms to maximize motion system performance, while its universal servo drive technology enables the system designer to easily control most types of motors and stages.



CONFIDENCE

Leverage 30+ years
of high-performance
motion control expertise



FLEXIBILITY

Control various motion
stage technologies



PERFORMANCE

Achieve a competitive advantage
with higher throughput and accuracy

For the latest version of this document visit our website at www.acsmotioncontrol.com

Smarter Motion

ACS
MOTION CONTROL

Specifications

Logic Supply Input

- Voltage range: 24 VDC +/-5%
- Maximum Input Current: 2A @ 22.8VDC
- Protections: Reverse Polarity

Drive Supply Input

- Voltage Range: 12-150VDC
- Maximum Input Current: Load Dependent

Amplifiers

- Number of Axes: 1
- Type: PWM 3-phase power bridge
- Motor Support
 - DC brush
 - 2 and 3 phase DC Brushless
 - 2 and 3 phase stepper: Open or closed loop, up to 1024 microsteps per step, dynamic current adjustment
- Output current: 2.5/5A, 5/10A, 10/20A, 15/30A at 100VDC only (continuous/peak, sine amplitude)
- Peak Current Time: 1 second
- PWM Switching Frequency: 20 kHz
- Minimum Load Inductance: 12.5 μ H per phase at 24VDC bus (contact ACS to discuss applications with lower phase inductance motors)
- Max Output Voltage: 97% of Drive Supply input voltage
- Max Output Power:
 - 316/629W (continuous/peak) for 2.5/5A
 - 633/1258W (continuous/Peak) for 5/10A
 - 1266/2517W (continuous/Peak) for 10/20A
 - 1208/2393W (continuous/Peak) for 15/30A
- Protections: Short Circuit, Overcurrent, Overtemperature, Overvoltage, Undervoltage

EtherCAT

- Interface: Dual RJ-45, 100BASE-TX
- Communication Profiles: CoE, FoE
- Device Profiles: DS402 (CiA402)
- Modes of Operation: CSP, CSV, CST, Homing, Profile Position, Profile Velocity Mode
- PDO Mapping: User-configurable, up to 128 bytes
- Max Cycle Rate: 4 kHz
- May operate as a slave under any EtherCAT master using the DS402 protocol, as well as any ACS EtherCAT master.
- Contact ACS for details: sales@acsmotioncontrol.com

Communication Interfaces

- SPI: 8 word (16 bits per word) 4 MHz bi-directional master/slave interface for data input to / output from custom servo algorithms
- Ethernet: 100 Mbps
- RS-232: Up to 115200 bps

Servo Control Algorithms

- Standard
 - Cascaded PIVFF with loop shaping filters
 - Advanced feedforward
 - Dual loop
 - Disturbance rejection
 - Gain Scheduling
 - Field-oriented control
 - Space vector modulation
- Optional
 - Non-Linear Control
 - Custom algorithms to meet demands of unique applications (contact ACS)
- Loop Sampling and Update Rate: 20 kHz position, 20 kHz velocity, 20 kHz current

Feedback

- Incremental
 - AqB Encoders (Default type)
 - Max Frequency: 50 MHz
 - Electrical Interface: RS-422
 - Error Detection: Encoder not connected, illegal transition
 - SinCos Encoders (Optional)
 - Max Frequency: 500 kHz or 10 MHz, according to ordering option
 - Electrical Interface: 1 V peak to peak +/-10%
 - Max Multiplication: 4,096 (per full signal period)
 - Error Detection: Not connected
 - Max Multiplication: 65,536 (per full signal period)
 - Compensation: Phase, Gain, Offset
 - Note: The drive automatically generates a digital quadrature echo of the SinCos encoder signal and sends it as an output to the AqB encoder pins
 - Digital Hall Sensor Inputs
 - Qty: 3 per axis
 - Electrical Interface: 5V, Single-ended, source, opto isolated
 - Note: Used for initial commutation, not for position servo feedback
 - Limit Sensor Inputs (Usable as general purpose)
 - Qty: 2
 - Electrical Interface: 5/24V \pm 20%, opto-isolated, sink or source (jumper selectable)
- Absolute (Optional)
 - Types: BiSS-C, EnDat 2.1 & 2.2, Smart-Abs, SSI, Sanyo Denki, Panasonic A4
 - Max Frequency: EnDat- 2MHz, Smart-Abs-2.5MHz, Biss-C- 10MHz, Panasonic- 2.5MHz, Sanyo- 2.5MHz
 - Electrical Interface: RS-485
 - Error Detection: CRC, timeout, encoder not ready
- Supply Output: 5.1V. Total available current 1.5A for all analog encoders and 1.5A for all digital encoders
- ID Chip Interface: 1 per axis. For identification of compatible stages' configuration parameters.

For the latest version of this document visit our website at www.acsmotioncontrol.com

Smarter Motion


MOTION CONTROL

Specifications Continued

Digital I/O (All are useable as general purpose)

- High-Speed Position Capture (MARK) Input
 - Qty: 1
 - Electrical Interface: 5/24V $\pm 20\%$, Opto-isolated, two terminals
 - Max Capture Frequency: 2 kHz
- General Purpose Input
 - Qty: 1
 - Electrical Interface: 5/24V $\pm 20\%$, Opto-isolated, two terminals
 - Max Capture Frequency: 2 kHz
- Limit Sensor Inputs
 - Qty: 2 (See Feedback section for more details)
- High-Speed Position Event Generation (PEG) Outputs
 - Qty: 1
 - Electrical Interface: RS-422
 - Max Pulse Frequency: 10 MHz
 - Pulse Width Range: 40 ns to 671 ms
- Motor Brake Output
 - Qty: 1
 - Electrical Interface: 5/24V $\pm 20\%$, opto-isolated, sink or source (jumper selectable)
 - Output Current: 100 mA
 - Max Update Frequency: 4 kHz
- General Purpose Output
 - Qty: 1
 - Electrical Interface: 5/24V $\pm 20\%$, opto-isolated, sink or source (jumper selectable)
 - Output Current: 100 mA
 - Max Update Frequency: 4 kHz

Standards and Certifications

- CE Self Declaration: Yes (Pending)
- CE Electrical Safety: IEC61800-5-1 (Pending)
- CE EMC: EN 61800-3 (Pending)
 - UL Electrical Safety: UL 61800-5-1 (Pending)
 - STO Functional Safety: IEC 61800-5-1, IEC 61800-5-2 (Pending)
 - SS1 Functional Safety: IEC 61800-5-1, IEC 61800-5-2 (Pending)
 - EtherCAT Technology Group Conformance Tested: Pending

Analog I/O (All are useable as general purpose)

- Analog Input
 - Quantity: 1
 - Electrical Interface: $\pm 10V$ differential or 0-10V single ended
 - Resolution: 16 bit
 - Input Frequency: 5 kHz
- Analog Outputs
 - Electrical Interface: $\pm 10V$ differential
 - Resolution: 10 bit - Max Ripple: 25 mV
 - Max Load: 10 kOhm
 - Max Update Frequency: 1 kHz

Profile Generation

- 3rd order with smooth on-the-fly endpoint modification

Real-Time Programming

- Language: ACSPL+ object-oriented multi-threading
- Number of User-Programmable Buffers (Threads): 4
- Max Program Cycle Rate: 4 kHz
- Max Data Collection Rate: 20 kHz up to 4 variables
- RAM: 256MB • Flash: 1GB

Physical

- Dimensions: 128x139x55mm
- Weight: < 600g
- Environmental
 - Rated Operational Temperature: 0° to 50°C
 - Humidity: 5 to 90% non-condensing humidity
 - Storage and Transportation Temperature Range: -25° to 60°C
 - Shock: 50 m/s² (5 G)
 - Vibration: 10 m/s² (1 G)

Optional Accessory Products

- XDMsa-ACC1: Mating Connector Kit
- STO-ACC1: STO Breakout Cable
- SPI-ACC1: SPI Breakout Cable
- RS232-ACC1: RS232 Adapter Cable

Functional Safety I/O (Optional)

- Safe Torque Off (STO) Input
 - Electrical Interface: Dual-channel 24V isolated
 - Safety Standards: See Standards and Certifications Section
- Safe Stop 1 (SS1) Feature
 - Deceleration time till STO activation: 110-230ms.
 - Exact deceleration time value is fixed (SS1-t functionality) and depends on product configuration (see user manual for more details)

Ordering Options

Ordering Options	Field	Example User Selection	Values
Drive Axes	1	1	1
Current and Bus Voltage Rating	2	C	A = 2.5/5A up to 150VDC B = 5/10A up to 150VDC C = 10/20A up to 150VDC D = 15/30A up to 100VDC
500 kHz SinCos Encoder Channels	3	1	0, 1, 2
10 MHz SinCos Encoder Channels	4	0	0, 1, 2
Absolute Encoder Channels	5	1	0, 1, 2
Functional Safety	6	T	N=None, T=STO & SS1
Non-Linear Control	7	N	N = No, C = Non-Linear Control
Reserved for Future	8	N	N
Reserved for Future	9	N	N
Reserved for Future	10	N	N

Example: IDMSa-1C101-TNNNN

Description: 10/20A, 1 channel 500kHz SinCos, 1 channel absolute encoder, STO & SS1

Field	1	2	3	4	5	6	7	8	9	10
PN	1	C	1	0	1	T	N	N	N	N

For the latest version of this document visit our website at www.acsmotioncontrol.com

Smarter Motion

ACS
MOTION CONTROL